



H & M APC - 16 Adjustable Pipe Clamp



Here is one great tool that does the work of 12 cage-type clamps. The H&M APC-16 Adjustable Pipe Clamp comes complete and ready to align 2"- to 16"-diameter pipe.

Made of durable, ductile cast iron, the H&M APC-16 features convenient carrying handles and precisely machined V's for perfect pipe alignment every time. At only 31 lbs. it is also lightweight and easily portable to any job site. One person can position the clamp and start welding in about two minutes for most applications and pipe sizes.

Acme 3/4-6" threaded bolts and nuts tighten the pipe chain around the pipe. Each adjusting nut is fitted with its own handle. No extra tools or ratchet handles are needed. The Acme threaded bolts, nuts and chain are captive to the pipe clamp, eliminating any lost or misplaced items.



General Pipe Clamps

H&M offers General Pipe Clamps for 2"- to 60"-diameter pipe. Each is hinged for easy positioning around the pipe and available with flat  or arched  cross bars.

The Standard Pipe Clamp features a lever and a cam for tightening the clamp around both ends of adjoining pipe.

The Hydraulic Pipe Clamp employs an eight-ton hydraulic jack for opening and closing the clamp. This feature is especially important when aligning 16"- to 60"-diameter pipe.

The Ratchet Clamp includes precision-cut Acme thread design for strength and easy operation, plus an enclosed mechanism to prevent mud and dirt contamination. This clamp works on 10"- to 60"-diameter pipe.



NOTE: The H&M Adjustable Pipe Clamp and General Pipe Clamps are ONLY designed for aligning pipe ends while welding. DO NOT use these clamps to support the weight of a pipe being lifted or moved, and DO NOT use these clamps with shims, wedges or cheaters.


Ratchet Pipe Clamp









Standard Pipe Clamp



Hydraulic Pipe Clamp



Model		Pipe Sizes
Standard		2" to 60"
Standard No Tack		3" to 60"
Hydraulic		16" to 60"
Hydraulic No Tack		16" to 60"
Ratchet		10" to 60"
Ratchet No Tack		14" to 60"